



# CVR122-43

**Dual Voice Coil  
Subwoofer 30 cm**

**Power Handling  
400 Watts RMS / 800 Watts Max.**

## Recommended Enclosure

Sealed Box  
Sealed Volume: 45 L

## Recommended Enclosure

Ported Box  
Vented Volume: 49,6 L  
Port Area: 203 cm<sup>2</sup>  
Port Length: 51 cm

## Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	54 mm
Max. Linear Excursion	Xmax	+/- 14 mm
Cone Area	Sd	531 cm <sup>2</sup>
Moving Mass	Mms	164,57 g
DC Resistance	Re	2 x 1,8 Ohms
Resonance Frequency	Fs	32,6 Hz
Mechanical Q-Factor	Qms	8,166
Electrical Q-Factor	Qes	0,703
Total Q-Factor	Qts	0,648
Equivalent Air Volume	VAS	65,3 L
Flux Density	B/L	18,92 N/A
Efficiency 1W/1m	SPL	86,9 dB

## Mechanical Components

- Steel Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Polyimide Voice Coil Former

## Dimensions & Weight

External Diameter: 316 mm  
Mounting Diameter: 278 mm  
Mounting Depth: 159 mm  
Shipping Weight: 7,3 kg

