



S12L72-11

**Dual Voice Coil
Subwoofer 30 cm**

Power Handling
750 Watts RMS / 1500 Watts Max.

Recommended Enclosure

Ported Box
Vented Volume: 71 L
Port Area: 217 cm²
Port Length: 42 cm

Recommended Enclosure

Ported Box
Vented Volume: 49,6 L
Port Area: 217 cm²
Port Length: 57 cm

Technical Specifications

| | | |
|-----------------------|------|---------------------|
| Impedance | Zn | 2 x 2 Ohms |
| Voice Coil Diameter | Ø | 61 mm |
| Max. Linear Excursion | Xmax | +/- 14 mm |
| Cone Area | Sd | 645 cm ² |
| Moving Mass | Mms | 247,3 g |
| DC Resistance | Re | 2 x 1,7 Ohms |
| Resonance Frequency | Fs | 34,9 Hz |
| Mechanical Q-Factor | Qms | 6,26 |
| Electrical Q-Factor | Qes | 0,51 |
| Total Q-Factor | Qts | 0,5 |
| Equivalent Air Volume | VAS | 45,6 L |
| Flux Density | B/L | 18,264 N/A |
| Efficiency 1W/1m | SPL | 87,3 dB |

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Polyimide Voice Coil Former

Dimensions & Weight

External Diameter: 321 mm
Mounting Diameter: 281 mm
Mounting Depth: 173 mm
Shipping Weight: 11,7 kg

