



# S15L74-11

**Dual Voice Coil  
Subwoofer 38 cm**

**Power Handling**  
**1000 Watts RMS / 2000 Watts Max.**

## Recommended Enclosure

Ported Box  
Vented Volume: 127 L  
Port Area: 314 cm<sup>2</sup>  
Port Length: 38 cm

## Recommended Enclosure

Ported Box  
Vented Volume: 85 L  
Port Area: 263 cm<sup>2</sup>  
Port Length: 50 cm

## Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	66 mm
Max. Linear Excursion	Xmax	+/- 16 mm
Cone Area	Sd	1056 cm <sup>2</sup>
Moving Mass	Mms	328,1 g
DC Resistance	Re	2 x 3,5 Ohms
Resonance Frequency	Fs	26,3 Hz
Mechanical Q-Factor	Qms	6,58
Electrical Q-Factor	Qes	0,53
Total Q-Factor	Qts	0,49
Equivalent Air Volume	VAS	166 L
Flux Density	B/L	26,955 N/A
Efficiency 1W/1m	SPL	89,4 dB

## Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Dual Magnet 2 x 124,1 oz (7.036 g)
- Polyimide Voice Coil Former

## Dimensions & Weight

External Diameter: 397 mm  
Mounting Diameter: 349 mm  
Mounting Depth: 199 mm  
Shipping Weight: 17,2 kg

